

CS7410/Omni-ID Prox US ABS RFID Tags – Higgs3 version



Product Profile:

CS7410/Omni-ID Prox offers the smallest form factor and best performance of any UHF RFID tag on the market today. This short-range passive RFID tag has a managed read range greater than 8 feet. It is ideally suited for IT asset identification,



where increased visibility and asset registration are essential. As such, CS7410/Omni-ID Prox delivers unmatched precision for the tracking of smaller high-value assets, electronic devices, communications/network cards, servers, and other assets or applications that demand high performance. What's more, the tag's compact form factor and extremely small footprint make it a discrete solution for items with little available real estate.

Features:

- Ultimate reliability and accuracy on any material in any environment
- Increased visibility of assets and conveyances
- Improved efficiency in locating or auditing items
- Very small form factor
- Up to 3 meters read range (balanced) under U.S. standards
- Supplied with ruggedized rigid case (ABS)
- Size : 54.5mm x 16mm x 7.8mm

Specifications:

Physical Characteristics:	Ruggedized rigid case ABS IP68, Size : 54.5mm x 16mm x 7.8mm Weight: 5.3g
Attachment:	Manual and film adhesive (standard) Foam adhesive (optional)
Read Range:	Up to 3 meters balanced
Mode of operation:	Passive (battery free)
Frequency Range:	902 to 928 MHz
Protocol:	ISO18000-6C, EPC UHF Class 1 Gen 2
Memory Content:	Alien Higgs 3, 512 bits user memory
Environment:	Operating Temp: -20°C to +55°C
Quality assurance:	100% read tested
Order Code:	CS-7410