

CS7411/Omni-ID Flex US ABS RFID Tags Higgs3 version

Product Profile:

CS7411/Omni-ID Flex is a medium-range passive UHF RFID tag with a managed read range up to 5 meters – offering increased visibility of assets and stock/intermediates, and greater efficiency in manufacturing and retail environments.



The product delivers an outstanding performance-to-size ratio, while providing balanced on/off metal performance. These features are critical in the area of laptop tracking, where CS7411/Omni-ID Flex ensures accurate asset registration and security benefits.

Features:

- Ultimate reliability and accuracy on any material in any environment
- Increased visibility of assets and conveyances
- Improved efficiency in locating or auditing items
- Up to 5 meters read range (balanced) under U.S. standards
- Supplied with ruggedized rigid case v2 (ABS)
- Size : 100mm x 21mm x 7.2mm

Specifications:

Physical Characteristics:	Ruggedized rigid case v2 ABS IP68, Size: 100mm x 21mm x 7.2mm Weight: 11.6g
Attachment:	Manual (standard) Film adhesive (optional) Foam adhesive (optional)
Read Range:	Up to 5 meters balanced
Mode of operation:	Passive (battery free)
Frequency Range:	902 to 928 MHz
Protocol:	ISO18000-6C, EPC UHF Class 1 Gen 2
Memory Content:	Alien Higgs 3, 512 bits user memory
Environment:	Operating Temp: -20°C to +55°C
Quality assurance:	100% read tested
Order Code:	CS-7411